LX型整体螺旋稳定器

Spiral Drilling Stabilizer Type LX



LX型整体螺旋稳定器分为钻柱型和井底型。该产品在螺旋棱带上敷焊硬质合金，具有硬度高、韧性好、耐磨性强、使用寿命长等特点。

Model “LX" Integral Spiral Stabilizer is divided into drill string model and near bit model. This product welded carbide in the spiral rib belt . It's characterized by high hardness, good toughness and wear resistance, as well as long service life.

Specifications

型号 Model	上端螺纹Upper thread API	下端螺纹 Down thread API	总长 Overall length (mm)	两端外径 O.D. of both ends mm(in)	水眼 I.D. (mm)	工作外径 O.D. (mm)	适用钻头直径Suitable bit mm (in)	有效稳定长度 efficient stable length mm(in)
LX152HF3—121	NC38	NC38	1825	121 (4-3/4)	50.8 (2)	152 (6)	152.4 (6)	400 (15.74)
LX152HF3—121NB	NC38	3 1/2REG	1670					
LX164HF3—121	NC38	NC38	1845	121 (4-3/4)	50.8 (2)	164 (6.46)	165.1 (6 -1/2)	400 (15.74)
LX164HF3—121NB	NC38	3 1/2REG	1690					
LX215HF3—171	NC50	NC50	1845	171 (6-3/4)	71.4 (2.8)	215 (8.46)	215.9 (8 -1/2)	406 (15.98)
LX215HF3—171NB	NC50	4 1/2REG	1695					
LX240HF3—171	NC50	NC50	1940	171 (6-3/4)	71.4 (2.8)	240 (9.45)	241.3 (9 1/2)	450 (17.72)
LX240HF3—171NB	NC50	4 1/2REG	1785					
LX311HF3—203	6 5/8REG	6 5/8REG	2060	203 (8)	71.4 (2.8)	311 (12.24)	311.1 (12 -1/4)	500 (19.68)
LX311HF3—203NB	6 5/8REG	6 5/8REG	1910					
LX444HF3—241	7 5/8REG	7 5/8REG	2320	241 (9-1/2)	76.2 (3)	444 (17.5)	444.5 (17-1/2)	600 (23.62)
LX444HF3—241NB	7 5/8REG	7 5/8REG	2170					
LX660HF3—241	7 5/8REG	7 5/8REG	2700	241 (9-1/2)	76.2 (3)	660 (26)	660.4 (26)	600 (23.62)
LX660HF3—241NB	7 5/8REG	7 5/8REG	2550					

Add: 66 Nantiancheng Road,xiangcheng District,Suzhou,China

Email: lily.zhang@quickoilfield.com Mobile/Whatsapp:+8613182677210 Web: www.quickoilfield.com

YTLX型 液压可变径稳定器

Hydraulic Adjustable Stabilizer Type YTLX

YTLX型液压可变径稳定器是一种新型的钻井用调径扶正器，该调径扶正器是利用钻压将扶正器的活塞推出，达到调径目的，当起钻或上提钻具时，扶正器的活塞即会自动缩回，防止起下钻时发生遇阻或遇卡现象发生。该扶正器结构简单，耐磨性好，调径范围大，可适用井眼扩大的情况。尤其适用于定向钻井和水平钻井作业。



Model YTLX hydraulic adjustable stabilizer is a new kind of adjustable stabilizer for well drilling. The adjustable stabilizer pushes out its piston by the drilling pressure to adjust its diameter. When drilling or lifting the drilling tools, its piston will retract automatically to prevent blockage or jamming phenomenon. Because of simple structure, good abrasion resistance, and wider adjustable diameter range, the stabilizer can be used to expand the hole, especially suitable for directional drilling and horizontal drilling.

Specifications

规 格 Specification	稳定器两端外径 mm(in) Stabilizer O.D. on both ends	连接螺纹 Connection	水眼 mm(in) Water Hole	调径范围mm (in) Adjustable diameter scope	适用钻头直径（in） Applicable bit diameter
YTLX216HF4-178	178(7)	NC50	57(2 1/4)	203～216 (8～8 1/2)	8 1/2
YTLX311HF4-203	203(8)	6 5/8REG	71(2 3/4)	298～311 (11 3/4～8 1/2)	12 1/4
系统压力 System Pressure	30MPa				
工作环境温度 Working Temperature	≤120。C				

Add: 66 Nantiancheng Road,xiangcheng District,Suzhou,China

Email: lily.zhang@quickoilfield.com Mobile/Whatsapp:+8613182677210 Web: www.quickoilfield.com