



Quick Oilfield Supply Co.,Ltd

www.quickoilfield.com Email: lily.zhang@quickoilfield.com

Casing catalogue





Quick Oilfield Supply Co.,Ltd

www.quickoilfield.com Email: lily.zhang@quickoilfield.com



Casing technical parameter:

Keywords: API 5CT Steel Pipe, J55,K55,L80,N80Q,C90,T95,P110 Oil/Petroleum Casing Pipe, OCTG

- 1) Grade: J55,K55,L80,N80Q,C90,T95,P110
- 2) Size: 4 1/2", 5", 5 1/2", 6 5/8", 7", 7 5/8", 9 5/8", 10 3/4", 13 3/8", 16", 18 5/8", 20"
- 3) Wall thickness: 0.205 – 0.635 inch
- 4) Thread type: STC, LTC, BTC
- 5) Length: R1,R2,R3
- 6) All our casings accord with API 5CT standard, and we get the right to use the API 5CT LOGO.

Seamless casing specification (API5CT)

Outside diameter	Normal Weight	Wall Thickness	Grade and connection type				
			J55 K55	L80 C95	N80	C90 T95	P110
4 1/2	9.5	0.205	PS	-	-	-	-
	10.5	0.224	PSB	-	-	-	-
	11.6	0.25	PSLB	PLB	PLB	PLB	PLB
	13.5	0.29	-	PLB	PLB	PLB	PLB
	15.1	0.337	-	-	-	-	PLB
5	11.5	0.22	PS	-	-	-	-
	13	0.253	PSLB	-	-	-	-
	15	0.296	PSLB	PLB	PLB	PLBE	PLB
	18	0.362	-	PLB	PLB	PLBE	PLB
	21.4	0.437	-	PLB	PLB	PLB	PLB
	23.2	0.478	-			PLB	
5 1/2	14	0.244	PS	-	-	-	-
	15.5	0.275	PSLB	-	-	-	-
	17	0.304	PSLB	PLB	PLB	PLBE	PLB
	20	0.361	-	PLB	PLB	PLBE	PLB



Quick Oilfield Supply Co.,Ltd

www.quickoilfield.com Email: lily.zhang@quickoilfield.com

	23	0.415	-	PLB	PLB	PLBE	PLB
6 5/8	20	0.288	PSLB	-	-	-	-
	24	0.352	PSLB	PLB	PLB	PLBE	PLB
	28	0.417	-	PLB	PLB	PLBE	PLB
	32	0.475	-	PLB	PLB	PLBE	PLB
7	17	0.231	-	-	-	-	-
	20	0.272	PS	-	-	-	-
	23	0.317	PSLB	PLB	PLB	PLBE	-
	26	0.362	PSLB	PLB	PLB	PLBE	PLB
	29	0.408	-	PLB	PLB	PLBE	PLB
	32	0.453	-	PLB	PLB	PLBE	PLB
	35	0.498	-	PLB	PLB	PLBE	PLB
7 5/8	38	0.54	-	PLB	PLB	PLBE	PLB
	24	0.3	-	-	-	-	-
	26.4	0.328	PSLB	PLB	PLB	PLBE	PLB
	29.7	0.375	-	PLB	PLB	PLBE	PLB
	33.7	0.43	-	PLB	PLB	PLBE	PLB
	39	0.5	-	PLB	PLB	PLBE	PLB
	42.8	0.562	-	PLB	PLB	PLB	PLB
	45.3	0.595	-	PLB	PLB	PLB	PLB
8 5/8	47.1	0.625	-	PLB	PLB	PLB	PLB
	24	0.264	PS	-	-	-	-
	28	0.304	-	-	-	-	-
	32	0.352	PSLB	-	-	-	-
	36	0.4	PSLB	PLB	PLB	PLBE	PLB
	40	0.45	-	PLB	PLB	PLBE	PLB
	44	0.5	-	PLB	PLB	PLBE	PLB
9 5/8	49	0.557	-	PLB	PLB	PLBE	PLB
	32.3	0.312	-	-	-	-	-
	36	0.352	PSLB	-	-	-	-
	40	0.395	PSLB	PLB	PLB	PLBE	-
	43.5	0.435	-	PLB	PLB	PLBE	PLB
	47	0.472	-	PLB	PLB	PLBE	PLB
	53.5	0.545	-	PLB	PLB	PLBE	PLB
10 3/4	58.4	0.595	-	PLB	PLB	PLB	PLB
	32.75	0.279	-	-	-	-	-
	40.5	0.35	PSB	-	-	-	-
	45.5	0.4	PSB	-	-	-	-
	51	0.45	PSB	PSB	PSB	PSBE	PSB
	55.5	0.495	-	PSB	PSB	PSBE	PSB
	60.7	0.545	-	-	-	PSBE	PSB
	65.7	0.595	-	-	-	PSB	PSB
13 3/8	48	0.33	-	-	-	-	-
	54.5	0.38	PSB	-	-	-	-



Quick Oilfield Supply Co.,Ltd

www.quickoilfield.com Email: lily.zhang@quickoilfield.com

	61	0.43	PSB	-	-	-	-
	68	0.48	PSB	PSB	PSB	PSB	PSB
	72	0.514	-	PSB	PSB	PSB	PSB
	65	0.375	-	-	-	-	-
16	75	0.438	PSB	-	-	-	-
	84	0.495	PSB	-	-	-	-
	109	0.656	P	P	P	-	P
	87.5	0.435	PSB	-	-	-	-
18 5/8	94	0.438	PSLB	-	-	-	-
20	106.5	0.5	PSLB	-	-	-	-
	133	0.635	PSLB	-	-	-	-

*Premium connections are available on request. P - plain end, S – short round thread, B- butress, L- long round thread

Electric Resistance Welding (ERW) casing specification

Outside diameter	Nomal Weight	Wall Thickness	Grade	Connection type
in	lb/ft	in	J55	
			K55	
5 1/2	14	0.244	J55/K55	PS
	15.5	0.275	J55/K55	PSLB
	17	0.304	J55/K55	PSLB
6 5/8	24	0.352	J55/K55	PSLB
7	20	0.272	J55/K55	PS
	23	0.317	J55/K55	PSLB
	26	0.362	J55/K55	PSLB
8 5/8	24	0.264	J55/K55	PS
	28	0.304	J55/K55	PS
	32	0.352	J55/K55	PSLB
	36	0.4	J55/K55	PSLB
9 5/8	36	0.352	J55/K55	PSLB
	40	0.395	J55/K55	PSLB
10 3/4	40.5	0.35	J55/K55	PSB
	45.5	0.4	J55/K55	PSB
13 3/8	54.5	0.38	J55/K55	PSB
	68	0.48	J55/K55	PSB

* P - plain end, S – short round thread, B- butress, L- long round thread